

APPARATUS AND METHOD FOR INPUTTING
COORDINATE INFORMATION TO A COMPUTING
DEVICE

RELATED APPLICATION

The present Application is related to Provisional Patent Application filed 25 May 2000 and assigned serial number 60/206,907, entitled "Novel PC Mouse."

FIELD OF THE INVENTION

This invention relates to an apparatus and method for inputting coordinate data to a computing device and, in particular, to a method for inputting such information via a stationary computer peripheral input device.

BACKGROUND OF THE INVENTION

There are many software applications which simulate sporting games. Virtual sporting games need a mechanism for inputting movement coordinates. It is therefore an object of the present invention to provide such a inputting mechanism.

BRIEF SUMMARY OF THE INVENTION

An input device apparatus for providing coordinate data indicative of the motion of an object to a computing apparatus, includes an elongated member translatable along and rotatable about a longitudinal axis, a swing arm attached to the object and to the elongated member such that movement of the object

results in corresponding movement of the elongated member, and an engagement surface for engaging an input device of the computing apparatus.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a perspective diagrammatical view of the basic elements of the present invention;

5 Fig. 2 is a preferred embodiment of the present invention;

Fig. 3 is a more detailed view of the apparatus of Fig. 2 showing a pivot point;

Fig. 4 is a perspective view of the bracket and a mouse holder arm in an open position;

10 Fig. 5 is a view of the bracket and mouse holder arm of Fig. 4 in a closed position;

Fig. 6 shows an application of the embodiment of Fig. 2 as a putting station;

Fig. 7 shows an alternative embodiment of the apparatus of Fig. 2; and

15 Fig. 8 shows an application of the embodiment of Fig. 7 as a tee ball station;

DETAILED DESCRIPTION OF THE INVENTION

There is shown in Fig. 1 a perspective diagrammatical view of the basic elements of the present invention. An elongated member 11, here shown as a cylinder having a circular cross section, is supported such that movement along

5

25

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995

In a preferred embodiment, motion of an object 31 is coupled to the elongated member 11 as shown in Fig. 2. In the illustration provided, the object 31 is configured as a golf ball, and forms part of a putting system 20. Generally, the object 31 is configured as a spherical item used in a competitive sport, such as a baseball, a golf ball, or a soccer ball. The object 31 is attached to a distal end 37 of a swing arm 33 which, in turn, is mechanically coupled to the elongated member 11 at a proximal end 39. The coupling between the swing arm 33 and the elongated member 11 is such that, when the swing arm 33 rotates about the longitudinal axis 13 (i.e., moves into and out of the plane of the Figure), the elongated member 11 likewise rotates about the longitudinal axis 13. The coupling between the swing arm 33 and the elongated member 11 is additionally such that, when the swing arm 33 rotates in a plane containing the longitudinal axis 13 (i.e., moves in the +Z and -Z directions indicated by the arrow 35), the elongated member 11 moves in the +X and -X directions, along the longitudinal axis 13.

In a preferred embodiment, the mechanical coupling between the swing arm 33 and the elongated member 11 is achieved by means of a pivoting element 41 comprising a first arm 43, a cross piece 45, and a second arm 47. The first arm 43 is substantially parallel with the longitudinal axis 13 and is attached to the elongated member 11 such that axial translation of the first arm 43 (i.e., in the +X and -X directions) results in the same axial translation of the elongated member 11. In the configuration shown, the first arm 43 is rotatable about the longitudinal axis 13.

In a preferred embodiment, the second arm 47 is substantially parallel to the first arm 43. The second arm 47 is connected to the swing arm 33 at a pivot point 49 such that the swing arm 33 is free to rotate in the +Z and -Z directions while being coupled to the second arm 47, as described in greater detail below.

5 Translation of the second arm 47 in the +X and -X directions results in corresponding movement of the elongated member 11 along the longitudinal axis 13.

10 The crosspiece 45 provides a rigid connection between the first arm 43 and the second arm 47 such that movement of the second arm 47 in the +X and -X directions results in equivalent movement of the first arm 43 along the longitudinal axis 13. Additionally, when the swing arm 33 rotates about the longitudinal axis 13, the second arm 47 moves in a circular path having a center of rotation on the longitudinal axis 13.

15 The elongated member 11 is secured to a stationary bracket 29 which provides for appropriate placement of the object 31. For example, if the object 31 is intended to simulate a golf ball, the length of the swing arm 33 and the height of the bracket 29 are specified such that the height of the object 31 above the ground corresponds to the height of a golf tee. A holder arm 27 is pivotally connected to the bracket 29 so as to allow installation of the mouse 21 so that
20 the rotatable ball 23 is held against the elongated member 11 at the point of contact 19. A tension spring 51 provides a compression force for retaining the mouse 21 between the holder arm 27 and the bracket 29.

A typical application of the putting system 20 allows a person with a golf club to practice putting or driving swings by hitting the object and viewing the

results on an electronic display (not shown), such as a computer screen for example. When struck with the golf club, the object 31 is caused to spin about the longitudinal axis 13 in the +Y or the -Y direction, depending on whether the person is right- or left-handed. This motion is imparted to the elongated member 11 as a rotation about the longitudinal axis 13. If the object 31 is not struck 'head on,' the swing arm 33 will also swing in the +Z or -Z direction. This swinging is imparted to the elongated member 11 as a movement in the +X or the -X direction. Thus, by using the signals provided by the mouse 21 when the object is caused to move, the motion of the object can be simulated on the electronic display attached to the signal output wire 25, as described in greater detail below.

There is shown in Fig. 3 an alternative embodiment of a putting system 50. The putting system 50 includes a mouse holder arm 57 pivotally attached to a stationary bracket 59. A piece of elastomeric material 63 is attached to the mouse holder arm 57 such that a cushion is provided when the mouse holder arm 57 is retained against the mouse 51 by a ratchet mechanism 61. Release of the ratchet mechanism 61 allows the mouse holder arm 57 to spring away from the bracket 59 and the mouse 51 to be removed.

The swing arm 33 is coupled to the second arm 47 of the pivoting element 41 by means of a pin 69 passing through the swing arm 33 and the second arm 47. Movement of the swing arm in the +Z and the -Z directions may be restricted by guide surfaces 65 and 67. Fig. 4 shows the mouse holder arm 57 in a raised position, and also shows the position of the elongated member 11 in the

bracket 59. When the mouse holder arm 57 is closed, as shown in Fig. 5, the mouse 51 is retained against the bracket 59, as described above.

Fig. 6 shows a player 75 using a putting system 70 for an entertainment application. The player 75 uses a golf club 77 to strike the object 31 which moves in response as described above. In response, the putting system 70 transmits signals to a personal computer 79 along a signal output line 71. The personal computer 79 includes software to process the signals and produces a display 73 simulating the motion of a golf ball along a miniature green. Additional software may provide for scoring, sound effects, multiple players, and other features known to one skilled in the relevant art.

Fig. 7 illustrates an alternative embodiment of the inventive apparatus. A batting system 80 includes a counterweight 85 attached to a swing arm 83 such that the swing arm 33 is normally oriented with the object 31 in a raised position rather than suspended as in the above-described embodiments. This configuration allows use of a baseball, or a tee ball, as shown in Fig. 8. A player 95 uses a bat 97 to strike the object 31, here shown as a baseball. The counterweight 85 serves to maintain the object 31 at a 'batting' height. When the object 81 is struck, the electronic microprocessor in the mouse transmits data signals to a personal computer 99 which produces a display 93 for viewing by the player 95.

In yet another alternative embodiment, the output of the electronic microprocessor in the mouse 51 is reprogrammed so as to provide data signals to handheld electronic devices, such as an electronic game with a display

screen. In still another embodiment, only the electronic microprocessor of the mouse is used to produce data signals.

Alternatively, the swing arm 83 can be positioned such that a longitudinal axis 87 is vertical. In such a configuration (not shown), a soccer ball can be used in place of the object 81, where the player kicks the soccer ball horizontally to effect action in the game.

While the invention has been described with reference to a preferred embodiment, it will be understood by those skilled in the relevant art that various changes may be made and equivalents may be substituted for elements thereof without departing from the scope of the invention. In addition, many modifications may be made to adapt a particular situation or material to the teachings of the invention without departing from the essential scope thereof. Therefore, it is intended that the invention not be limited to the particular embodiment disclosed as the best mode contemplated for carrying out this invention, but that the invention will include all embodiments falling within the scope of the appended claims.